


# MO-Band User Manual

Version 2.0



**MO-BAND**



**MO-Key**

# MO-Band User Manual

Version 2.0

## Quick Start

1. Download and install S-Motion software from download portal.
2. Open S-Motion.
3. Plug MO-Key into any of your computer's USB port.
4. Press and hold side button to turn on MO-Band, the LED on MO-Band should turn solid blue.
5. Pair MO-Band with MO-Key by pressing the button on MO-Key, make sure your MO-Band is close enough to MO-Key (less than 5 inches).
6. Once paired, the LED on MO-Band should turn solid green, and you should see the data flowing into S-Motion.
7. Calibrate MO-Band's magnetometer by press and hold both the top button and side button on MO-Band, once the LED blink red, start and keep drawing figure-8 in the air until the LED turns back to solid green, the whole process takes about 15s.
8. Do the motion-to-MIDI mapping on S-Motion, and start crafting your sound.
9. Once you've done using MO-Band, power it off by pressing and holding the side button until the LED goes out.

## Features

### Bypass/Unbypass control

- Press on top button.

### S-Motion Mapping Mode Switch

- Double press top button.

### Check Battery Status

- Press on side button.

### Unpair with MO-Key

- Press and hold side button until LED turns to solid blue

## FAQ

### How do I charge MO-Band?

- Simply charge it with any USB-C cable via the USB-C port, you can plug the cable into any of your computer's USB port, or use one of your mobile phone's power adapter.

### Do I need to do the pairing every time I use MO-Band?

- No, the MO-Key will remember the paired MO-Band and connect to it automatically, you'll only need to redo the pairing after manually unpair them.

### When do I need to redo the magnetometer calibration?

- You would only need to redo it once you saw unstable data on z axis from S-Motion, it happens mostly because of the change of location (e.g. from your home to the venue you perform).